




ROBOTIC ACTUATORS

D80 (CM.1.2.1.1)

Specifications




ASBISc Enterprises PLC
1, Iapetou Street Agios Athanasios,
4101 Limassol, Cyprus

www.asbis.com

+357 25 857 000
m.zakharanka@asbis.com

		D80
		CM.1.2.1.1
PHYSICAL PROPERTIES		
Mass		1.12 kg
Hollow shaft diam.		9.5 mm
Rated torque		49 Nm
Peak torque		66 Nm
Permissible static tilting moment		328 Nm
Permissible dynamic tilting moment		124 Nm
Gear ratio		101:1
Gear pitch diameter		1.7 inch (43 mm)
Max speed		35 RPM
Brakes holding torque		70 Nm
Fast rotating parts Inertia, If		5.70E-05 kg*m²
Slow rotating parts Inertia, Is		1.50E-04 kg*m²
INTERFACE		
Communication		EtherCAT, CoE, FoE
POWER		
Nominal voltage		48 V
Under-voltage limit		20 V
Over-voltage limit		60 V
OUTPUT POSITION SENSOR		
Fast (motor) shaft position sensor		Absolute magnetic encoder
Output position sensor		Dual absolute multi-turn magnetic encoder with backup battery input (3.7V lithium)
Output position resolution		19 bit
Position accuracy		0.005 deg (Calibrated against external encoder)
OTHER		
Brakes		Magnetic clutch
PWM frequency		20 kHz
Current/velocity loop frequency		20 kHz
Working modes		Synchronous cyclic torque/synchronous cyclic velocity with feed-forward
Protection		Comm. cycle time/over-current/over-voltage/under-voltage/motor over-temperature/switches over-temperature
Standard safety functions		STO and FSoE
Lifetime (rated), h		10000 (At nominal torque)
SOFTWARE		
Controller features		Cogging torque compensation, output position calibration map, dynamic current limits, current feed-forward, redundant output position feedback, output encoder eccentricity compensation, hardware torque-off during undervoltage
Control software		Tunning utility/GUI (Windows/Linux), C/C++/python examples using open-source SOEM EtherCAT master
CONNECTORS		
Power terminals		M3 standoffs (suitable for M3 O-type terminals)
EtherCAT connectors		Molex PicoBlade 4-pin 1.25mm pitch
Multiturn battery connector		Molex PicoBlade 2-pin 1.25mm pitch
Load mounting		Axially oriented M3 bolts
ENVIRONMENT		
Operating temperature (environment)		0-50 deg C (When mounted on the heatsink > 400 cm²)
Operating temperature (case)		0-80 deg C
Operating ambient humidity (no condensation)		
Storage Temperature (no condensation)		
IP rating		IP30
Output shaft and bearings are sealed. IP could be improved up to IP65 by external housing		

D80 (CM.1.2.1.1)



- 1. DS power supply connection M3x5 max



ASBISC Enterprises PLC

1, Iapetou Street, Agios Athanasios,
4101, Limassol, Cyprus

www.asbis.com

+357 25 857 000

m.zakharanka@asbis.com