



Report No.: T1850408 05

TEST REPORT

NAME OF SAMPLE	2.4GHz Wireless Optical Mouse
TYPE	CNE-CMSW1X, CAMW-01X
TRADEMARK	/
CLIENT	Cho-Liang Thermal Tech Co., td
ADDRESS OF CLIENT	5F-3, NO.14, Lane 609, Sec.5, Chung Hsin Rd., San Chung City, Taipei County, Taiwan.R.O.C
INSPECTION CLASSIFICATION	Client Entrust
TEST ITEM	The operation of high & low temperature test


Shenzhen Alpha Product Testing Co., Ltd.
Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China



DECLARATIONS

1. The laboratory is with responsibility for the received sample and the result of the test can only reflect the evaluating of the sample. Therefore, the laboratory does not bear any liability for loss direct or indirectly caused to applicant by this result of the report.
2. The results relate only to the items tested.
3. This test report shall not be reproduced except in full without the written approval of our laboratory.
4. If there is any objection concerning the test data, the client should inform the issuing laboratory within 10 days from the date of the report under test return to the client.
5. This report is invalid when without special-purpose seal of testing report.
6. This report is invalid when without signatures of tester and approver
7. The number of this report is the same as the number of the relative original record.

Test Report

Name of sample	2.4GHz Wireless Optical Mouse	Report No.	T1850408 05
Client	Cho-Liang Thermal Tech Co., td	Address of client	5F-3, NO.14, Lane 609, Sec.5, Chung Hsin Rd., San Chung City, Taipei County, Taiwan.R.O.C
Means of receipt	Delivering	Inspection classification	Client Entrust
Quantity of sample	1 pc	Weight	58.0g
Sample characteristic and condition	See attachment of report.		
Test standard	According client requirements.		
Test result	No damage on product.		
Note	--		
Test report special-purpose seal	Tested by:		
	Approved by:		
	Date of issue	May 03, 2015	

Attachment of Report

The operation of high & low temperature test

Environment	Temperature: 24.8-25.2℃; Relative humidity: 49.2-58.2%
designation of samples	T150666
Test standard	According client requirements.
Test equipment	Temp. & Humid. Chamber
Testing requirements	Temp. condition: The samples in the working state, the operation in -20 degrees and 60 degrees respectively under the condition of 16 hours.
Test method	<ol style="list-style-type: none"> 1. Put the EUT with working status into the Temp. & Humid. Chamber as its intended position of use. 2. Adjust temperture to -20℃ in 1h. 3. Duration for 15h. 4. Adjust temperature to 60℃ in 1h. 5. Duration for 15h. 6. At the end of the testing, check Its function and appearance.
Test results	No abnormal function and no damage of appearance.
Verdict	Pass

Note: test eqitment

Equipment	Manufacturer	Model No.	Serial No.	Calibration date	Calibration due date
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-880	100631	2014.10.22	2015.10.21

Attachment of report – Photo

Photo 1


View:
sample
characteristics

- ☒ front
☐ rear
☐ right side
☐ left side
☐ top
☐ bottom
☐ internal

**Photo 2**

View:
sample
characteristics

- ☐ front
☒ rear
☐ right side
☐ left side
☐ top
☐ bottom
☐ internal



Attachment of report – Photo

Photo 3

View:
during temperature
test

☒ front

☐ rear

☐ right side

☐ left side

☐ top

☐ bottom

☐ internal

**Photo 4**

View:
Low temperature
test

☒ front

☐ rear

☐ right side

☐ left side

☐ top

☐ bottom

☐ internal



Attachment of report – Photo

Photo 5

View:
High temperature
test

- ☒ front
☐ rear
☐ right side
☐ left side
☐ top
☐ bottom
☐ internal

**Photo 6**

View:
after test

- ☒ front
☐ rear
☐ right side
☐ left side
☐ top
☐ bottom
☐ internal



--- End of report ---