

TEST REPORT

Report No: ECR1712120R-02

Applicant: Couso Technology Co., Ltd.

Address: No.26#, MinYe Street, TangXia Town, Dongguang City, GuangDong Province, China

Product: Wireless Keyboard & Mouse SET

Brand Name: COUSO, BANRUO

Model No: CS1000G, please see page 4 for mode list

Test Standards: ETSI EN301 489-1 v 2.1.1 (2017-02)
ETSI EN301 489-3 v 2.1.1 (2017-03)

Test result: The Testing has been performed on the submitted samples and found in compliance with the RED Directive 2014/53/EU requirements

Reviewer by

Approved by

Date of Report: Dec. 08, 2017

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at



Shenzhen SETEK Technology Co., Ltd.

1003, C Bldg, Fuyuan Business Trade Center 44 District Bao'an, Shenzhen, China

Website: www.setek.com.cn

E-mail: service@setek.com.cn

TEL: 86-755-26966362

FAX: 86-755-26966270

Table of Contents

1.0	General Details
1.1	Notes.....
1.2	Test Lab Details.....
1.3	Details of Applicant.....
1.4	Application Details.....
1.5	Test Item.....
1.6	Equipment Classification.....
1.7	List of Ports.....
1.8	Ancillary and Peripheral Devices.....
1.9	Test Standards.....
1.10	Test By.....
2.0	Technical Test
2.1	Summary of Test Result.....
2.2	Test Report.....
	Clause 8.2 Emission Test- Radiated Emissions.....
	Clause 8.4 AC Line Conducted Emissions.
	Clause 8.5 Harmonic Current Emissions.....
	Clause 8.6 Flicker and Voltage Fluctuation.....
	Clause 9.2 Immunity Test- Radiated, RF Electromagnetic Fields.....
	Clause 9.3 Electrostatic Discharge.....
	Clause 9.4 Fast Transient Common Mode.....
	Clause 9.5 RF Common Mode.....
	Clause 9.7 Voltage Dips.....
	Clause 9.8 Surge Common & differential Mode (1-phase).....
3.0	CE Label
4.0	Photograph-EUT
5.0	Test Equipments

1. General Information

1.1 Notes

The test results of this report relate exclusively to the test item specified in 1.5. The SETEK Lab does not assume Responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the SETEK Lab.

1.2 Testing Laboratory

Shenzhen SETEK Technology Co., Ltd.

1003, C Bldg, Fuyuan Business Trade Center, 44 District Bao'an, Shenzhen, China

Website: www.setek.com.cn E-mail: service@setek.com.cn

TEL: 86-755-26966362

FAX: 86-755-26966270

1.3 Details of Applicant

Name: Couso Technology Co., Ltd.

Address: No.26#, MinYe Street, TangXia Town, Dongguang City, Guangdong Province, China

1.4 Application Details

Date of Receipt of Application: Dec. 01, 2017

Date of Receipt of Test Item: Dec. 01, 2017

Date of Test: Dec. 01, 2017~ Dec. 07, 2017

1.5 Test Item

Manufacturer: Couso Technology Co., Ltd.

Address: No.26#, MinYe Street, TangXia Town, Dongguang City, Guangdong Province, China

Brand Name: COUSO, BANRUO

Model No.: CS1000G, CS2000G, CS3000G, CS4000G, CS4100G, CS4200G, CS4300G, CS4400G, CS4500G, CS4515G, CS4550G, CS4600G, CS4700G, CS4800G, CS4900G, CS5000G, CS5100G, CS5200G, CS5300G, CS5400G, CS5500G, CS5600G, CS5700G, CS5800G, CS5900G, CS-6000G, CS6100G, CS6200G, CS6300G, CS6400G, CS-6500G, CS6600G, CS6700G, CS6800G, CS6900G, CS7000G, CS7100G, CS7200G, CS7300G, CS7400G, CS7500G, CS7600G, CS7700G, CS7800G, CS7900G, CS8000G, CS8100G, CS8200G, CS8300G, CS8400G, CS8500G, CS8600G, CS8700G, CS8800G, CS8900G, CS-9000G, CS9100G, CS9200G, CS9300G, CS9400G, CS9500G, CS9600G, CS9700G, CS9800G, CS9900G, CX100LD, CX120LD, CX130LD, CX140LD, CX150LD, CX160LD, CX170LD, CX180LD, CX190LD, CK410B, CK910B, CS9100L, CS9200L, CS6500LD, CK470TL, CS4570G, CS4380G, CK400G, CK410G, CK420G, CK430G, CK440G, CK450G, CK460G, CK470T, CK480G, CK490G, CK510G, CK520G, CK530G, CK540G, CK550G, CK560G, CK570G, CK580G, CK590G, CK600G, CK601G, CK700G, CK710G, CK720G, CK730G, CK740G, CK750G, CK760G, CK770G, CK780G, CK790G, CM701G, CM702G, CM703G, CM704G, CM705G, CM706G, CM707G, CM708G, CM709G, CM710G,

The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

CM720G, CM730G, CM740G, CM750G, CM760G, CM770G, CM780G, CM790G, CM800LD, CM810LD, CM820LD, CM830LD, CM840LD, CM850LD, CM860LD, CM870LD, CM880G, CM890LD, CK920G, CK921G, CK923G, CK927G, CG10LD, CG11LD, CG12LD, CG13LD, CG14LD, CG15LD, CG16LD, CG17LD, CG18LD, CG19LD, CM610LD, CM620LD, CM630LD, CM640LD, CM650LD, CM660LD, CM670LD, CM680LD, CM690LD, CM610B, CM620B, CM630B, CM640B, CM650B, CM660B, CM670B, CM680B, CM690B, CM700B, CM710B, CM720B, CM730B, CM740B, CM750B, CM760B, CM770B, CM780B, CM790B, CM840B, CM850B, CM860B, CM870B, CM880B, CM890B, CM610G, CM620G, CM630G, CM640G, CM650G, CM660G, CM670G, CM680G, CM690G, CM810G, CM815G, CM820G, CM830G, CM840G, CM850G, CM860G, CM870G, CM880G, CM890G, CM891G, CM892G, CM893G, CM894G, CM895G, CM896G, CM897G, CM898G, CM898GL, CNS-HSETW3-RU, CNS-HSETW3-US, CNS-HSETW3-SK, CNS-HSETW3-LT, CNS-HSETW3-HU, CNS-HSETW3-BG, CNS-HSETW3-AD, CNS-HSETW3-CZ, CNS-HSETW3-UK, CNS-HKBW2-RU, CNS-HKBW2-US, CNS-HKBW2-SK, CNS-HKBW2-LT, CNS-HKBW2-HU, CNS-HKBW2-AD, CNS-HKBW2-CZ, CNS-HKBW2-EE, CNS-HKBW4-UK, CNS-HSETW4-RU, CNS-HSETW4-CS, CNS-HSETW4-US, CNS-HSETW4-BG, CNS-HSETW4-HU, CNS-HSETW4-LT, CNS-HSETW4-EE, GN-CS8400G, GN-CS8500G

The model(s) are all identical in interior structure, electrical circuits and components, and just the model names are different for the marketing requirement.

We prepare CS1000G for the test.

Description: 2.4GHz Wireless Keyboard & Mouse set

Additional Information

Frequency: 2408MHz-2474MHz for USB dongle and 2408MHz-2474MHz for keyboard Part and mouse Part

Channels: 34

Channel Separation: 2MHz

Modulation Type: GFSK

Antenna Designation: PCB Printed Antenna with maximum gain 1.2dBi for Keyboard/Mouse part and 1.0dBi for USB dongle part

Power Supply: DC1.5V for Tx (AAA for Keyboard, AA for Mouse) and DC5V for Rx (Host from PC)

Operation Distance: N/A

Resolution: N/A

Extreme Temp. Tolerance: -10°C to 55°C

Note: Classification according to CEPT/ERC Recommendation 70-03 & ETSI EN301 489-3 v 2.1.1 (2017-03)

a) Equipment Classification

Device Type 3

1.7 List of Ports

Port	Description	Classification ¹	Maximum cable Length	Cable Type
N/A				

Note ¹ports shall be classified as ac power, dc power or signal/control port.

²Maximum cable length corresponding to the appropriate ports shall be classified as $\leq 3\text{m}$ or $> 3\text{m}$.

1.8 Ancillary and Peripheral Devices

Description	Designation	Serial No.	Manufacturer
N/A			

List of Peripheral Devices Used for Testing

Description	Designation	Serial No.	Manufacturer
N/A			

Note: An Equipment (apparatus) used in connection with a receiver or transmitter is considered as an ancillary Equipment (apparatus) if:

- a. The equipment is intended for use in conjunction with a receiver or transmitter to provide additional operational and/or control features to the radio equipment. (e.g. to extend control to another position or location); and
- b. The equipment cannot be used on a stand alone basis to provide user functions independently of a receiver or transmitter; and
- c. The receiver or transmitter to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

1.9 Test Standards

ETSI EN 301 489-1 v 2.1.1 (2017-02)
Electromagnetic compatibility and Radio spectrum Matters (ERM);
Electromagnetic Compatibility (EMC) standard for radio equipment and services;
Part 1: Common technical requirements
ETSI EN 301 489-3 v 2.1.1 (2017-03)
ElectroMagnetic Compatibility (EMC) standard for radio equipment and services
Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 246
GHz; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

1.10 Test or Witness Test Engineering

Test By: Terry Tang
Printing Name: Terry Tang



2. Technical Test

2.1 Summary of Test Results

No deviations from the technical specification(s) were ascertained in the course of the tests Performed	
Final Verdict: (Only "Passed" if all Measurements are "Passed")	Pass

2.2 Test Report

Emission (EMI)

EMI Phenomenon	Port	Requirement		EUT Setup	Result	Applicability
		Standard	Basic Standard			
Conducted Interference Voltage	AC Mains	ETSI EN 301489-1: 2017-02 Clause 8.4	EN 55032:2015	Refer to Section 4	Complies	Applicable
Radiated Interference Field Strength 30~6000MHz	Enclosure	ETSI EN 301489-1: 2017-02 Clause 8.2	EN 55032:2015	Refer to Section 4	Complies	Applicable
Harmonic Current Emissions	AC Mains Input Port	ETSI EN 301489-1: 2017-02 Clause 8.5	EN 61000-3-2:2014	Refer to Section 4	Complies	Not Applicable
Flicker & Voltage Fluctuation	AC Mains Input Port	ETSI EN 301489-1: 2017-02 Clause 8.6	EN 61000-3-3:2013	Refer to Section 4	Complies	Not Applicable

The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

Immunity (EMS)

EM3 Phenomenon	Port	Requirement		EUT Setup	Result	Applicability
		Standard	Basic Standard			
Electronic Discharge (ESD)	Enclosure	ETSI EN 301 489-1: 2017-02 Clause 9.3	EN 61000-4-2: 2009	Refer to Section 4	Complies	Applicable
RF-Electro-Magnetic Field (80-6000MHz)	Enclosure	ETSI EN 301 489-1: 2017-02 Clause 9.2	EN 61000-4-3: 2006	Refer to Section 4	Complies	Applicable
Fast Transients, Burst	Power Line AC/DC	ETSI EN 301 489-1: 2017-02 Clause 9.4	EN 61000-4-4: 2012	Refer to Section 4	Complies	Applicable
Surge	Power Line (1 phase)	ETSI EN 301 489-1: 2017-02 Clause 9.8	EN 61000-4-5: 2014	Refer to Section 4	Complies	Applicable
Transients & Surge Vehicular Environment	Power Line (Car Charge)	ETSI EN 301 489-1: 2017-02 Clause 9.6	ISO 7637-1/2:1990	Refer to Section 4	Complies	Not Applicable
RF Common Mode (0.15-80MHz)	Power Line AC/DC signal Lines	ETSI EN 301 489-1: 2017-02 Clause 9.5	EN 61000-4-6: 2014	Refer to Section 4	Complies	Applicable
Vol. Dips, Interruptions& Fluctuations (AC Power)	Input& Output AC Ports only	ETSI EN 301 489-1: 2017-02 Clause 9.7	EN 61000-4-11 2004	Refer to Section 4	Complies	Applicable

N/A=Not Applicable

-Performance criteria A for immunity tests with phenomena of a continuous nature;

Communication between the Tx and Rx in the front of pings should not drop during the test.

-Performance criteria B for immunity tests with phenomena of a transient nature;

N/A

-Performance criteria C for immunity tests with power interruptions exceeding a certain time.

N/A

Note: For details see subclause 6.1 ETSI EN 301 489-3

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Uncertainty
Conducted Emissions	3.6dB
Radiated Emissions	4.7dB (Below 1GHz); 5.0dB (above 1GHz)
Harmonic Current Emission	1.2%
Voltage Fluctuations and Flicker	1.5%
Electrostatic Discharge	The waveform of voltage: 1.6%; Time: 3.1%
RF Electromagnetic Field	3.1dB
Electrical Fast Transients	The waveform of voltage: 1.5%; Time: 2.9%
Surge	The waveform of voltage: 1.5%; Time: 2.9%
RF Common Mode	3.9dB
Voltage Dips and Interruptions	The waveform of voltage: 1.5%; Time: 2.9%

Clause 8.2 Emission Test – Radiated Emission

This test assesses that ability of ancillary equipment to limit their internal noise from being radiated from the enclosure.

According to EMC basic standard (EN 55032)

Measurement according to EMC basic standard, The test results correspond to the 3m Semi-Anechoic Chamber results.

The EUT and its simulators are placed on a turntable which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to EN55032: 2015 on radiated measurement.


Radiated emissions were investigated over the frequency range from 30MHz to 1 GHz using a receiver bandwidth of 120kHz.

Radiated emissions were investigated over the frequency range from 30MHz to 6 GHz

Radiated Emission was performed at an antenna to EUT distance of 3 meters.

Radiated Emission Test

Block diagram of Test setup



Power line conducted Emission Limit

Frequency Range (MHz)	Distance (m)	Quasi-Peak limits (dB μ V/m)
30-230	10/3	30.0/40.0
230-1000	10/3	37.0/47.0
1000-3000	3	50 (AV) /70 (PK)
3000-6000	3	54 (AV) /74 (PK)

Note: The lower limit shall apply at the transition frequencies

Test result: N/A

Note: the test item not applicable to the EUT, because the test item is applicable to the enclosure of ancillary equipment

Clause 8.4 AC Line Conducted Emissions

According to EMC Basic Standard (EN 55032)

1. For the table top EUT the distance to the reference ground plane (wall) should be 40 cm.
2. AC input line plugged into LISN.

EUT Operating Mode

USB Dongle part under normal operation

Results

Power Line (L, N)	EUT Operating mode or operating mode no.	Detector (Peak, AV, QP)	Additional (scan-) Information (e.g. Pre-test Fast scan, Maxhold, Final measurement.)	Result (Passed / Failed)
L=>GND	USB Dongle part under	QP & AV		Pass
N=>GND	normal operation	QP & AV		Pass

The frequency spectrum from 0.15MHz to 30MHz was investigated. All readings are quasi -peak values with a resolution bandwidth of 9 KHz

Temperature: 23°C

Humidity: 50% RH

A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Dongle under Normal operation mode

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		20.3755	35.90	11.12	47.02	60.00	-12.98	QP	
2	*	20.3755	26.80	11.12	37.92	50.00	-12.08	AVG	

B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Dongle under Normal operation mode

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		20.0664	34.90	11.10	46.00	60.00	-14.00	QP	
2	*	20.0664	26.00	11.10	37.10	50.00	-12.90	AVG	

Remarks:

1. Uncertainty in conducted emission measured is 3.6dB.
2. QP and AV are abbreviations of quasi-peak and average individually.
3. The emission levels of other frequencies were very low against the limit.

Clause 8.5 Harmonic Current Emissions

This test was performed as per EMC Basic Standard EN61000-3-2 :2014

Environmental conditions: Temperature: 23°C; Humidity: 49%RH

EUT Operating Mode

Normal Operation

Results: N/A

Port	EUT Operating mode or operating mode no.	Result (Passed / Failed)
AC Input	Normal Operation	N/A

Please see the following test figure:

Table 1 - Limit of Harmonics Current Measurement	
Limits for Class A equipment	
Harmonics order (n)	Max. permissible harmonics current (A)
Odd harmonics	
3	2.3
5	1.14
7	0.77
9	0.40
11	0.33
13	0.21
15<=n<=39	0.15 x 15/n
Even harmonics	
2	1.08
4	0.43
6	0.30
8<=n<=40	0.23 x 8/n

Note:

- For Class A equipment, the harmonics of the input current shall not exceed the absolute values given in table 1.
- For Class B equipment, the harmonics of the input current shall not exceed the values given in table 1 multiplied by factor of 1, 5.

Table 2 - Limit of Harmonics Current Measurement	
Limits for Class C equipment	
Harmonics order (n)	Max. permissible harmonics current expressed as a percentage of the input current at the fundamental frequency (A)
Odd harmonics only	
2	2
3	$30 \times \lambda^*$
5	10
7	7
9	5
$11 \leq n \leq 39$	3

Note: The harmonic current limits of lighting equipment shall not exceed the relative limits given in table 2.

Table 3 - Limit of Harmonics Current Measurement		
Limits for Class D equipment		
Harmonics order (n)	Maximum permissible harmonic current per watt mA/W	Maximum permissible harmonic current A
Odd harmonics only		
3	3.4	2.30
5	1.9	1.14
7	1.0	0.77
9	0.5	0.40
11	0.35	0.33
$13 \leq n \leq 39$	$3.85/n$	See table 1
$11 \leq n \leq 39$	3	

Note: The harmonic of the input current shall not exceed the values that can be derived from table 3.

Test Equipment

Please refer to Section 6 this report.

Test Procedure

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The EUT is classified as follows:
 - Class A Balanced three-phase equipment and all other equipment, except that stated in one of the following classes.
 - Class B Portable tools.
 - Class C Lighting equipment, including dimming devices.
 - Class D Equipment having an input current with “special wave shape” and an active input power, $P \leq 600W$

The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

Note: Due to the DC operation of for the Keyboard and rated power less than 75W for the dongle. This test item not applicable.

Clause 8.6 Flicker and Voltage Fluctuation

This test was performed as per EMC Basic Standard EN 61000-3-3: 2013

Environmental conditions: Temperature: 23°C; Humidity: 49%RH

EUT Operating Mode

Normal Operation

Results

Port	EUT Operating mode or operating mode no.	Result (Passed / Failed)
AC Input	Normal Operation	N/A

Please refer to the following test figure

Test Equipment

Please refer to Section 6 this report.

Test Procedure

- a.. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- b. During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT 10 minutes and the observation period for long- term flicker indicator is 2 hours.

Note: Tests need not be made on equipment which is unlikely to produce significant voltage fluctuations or flicker.

Clause 9.2 Immunity Test – Radiated, RF Electromagnetic Field

According to EMC Basic Standard (EN 61000-4-3[9])

Environmental conditions: Temperature: 24°C; Humidity: 50%RH

USB Dongle part at Operating Mode and Keyboard/Mouse at Operating Mode

Type of Port: Enclosure

Performance Criterion: CT/CR

The distance between the turn-table axis and Tx&Rx-antenna is 3m.

Field strength = 3V/m

Start Frequency = 80MHz Stop Frequency = 6000MHz

Frequency Step = lin 1MHz

Modulation = AM, 400Hz, 1kHz, 80%

Results

Frequency (MHz)	Antenna Polarity	Radiation to	Reaction of the EUT During and after test	Result
80-6000	Horizontal	Front	No reactions recognized	Passed
80-6000	Vertical	Front	No reactions recognized	Passed
80-6000	Horizontal	Rear	No reactions recognized	Passed
80-6000	Vertical	Rear	No reactions recognized	Passed
80-6000	Horizontal	Left	No reactions recognized	Passed
80-6000	Vertical	Left	No reactions recognized	Passed
80-6000	Horizontal	Right	No reactions recognized	Passed
80-6000	Vertical	Right	No reactions recognized	Passed

Note: Performance criteria A observed.

Test Equipment

Please refer to Section 6 this report.

Test Procedure

The EUT and load, which are placed on a table that is 0.8 meter above ground, are placed with one coincident with

The calibration plane such that the distance from antenna to the EUT was 3 meters.

Both horizontal and vertical polarization of the antenna and four sides of the EUT are set on measurement.

Clause 9.3 Electrostatic Discharge

According to EMC basic standard (EN61000-4-2[10])

Environmental conditions: Temperature: 23°C; Humidity: 49%RH

USB Dongle part at Operating Mode and Keyboard/Mouse at Operating Mode

Type of Port: Enclosure, Key, Screw

Performance Criterion: TT/TR

For the table top EUT the distance to the reference ground plane should be 80 cm.

Direct contact discharge on conducting surfaces of EUT

Indirect air discharge on insulating surfaces of EUT

±2kV, ±4kV direct discharge & ±2kV, ±4kV, ±8kV air discharge

Test Results

Item	Contact Discharge to conducted surfaces and to coupling planes		Air Discharge at insulating surfaces
	Direct Contact Discharge	Indirect Contact Discharge	
Test Voltage	Reaction of EUT / Result		Reaction of EUT / Result
+2kV	n.r.r	Passed	n.r.r Passed
-2kV	n.r.r	Passed	n.r.r Passed
+4kV	n.r.r	Passed	n.r.r Passed
-4kV	n.r.r	Passed	n.r.r Passed
+8kV	-	-	n.r.r Passed
-8kV	-	-	n.r.r Passed

Remarks: n.r.r. = no reaction recognized

Performance Criteria A observed and No any function degraded during the tests.

Clause 9.4 Fast Transients Common Mode

According to EMC basic standard (EN61000-4-4 [11])

Environmental conditions: Temperature: 24°C; Humidity: 50%RH

USB Dongle Part at Operating Mode

Type of Port: AC mains power input/output port

Performance Criterion: TT/TR

For the table top EUT the distance to the reference ground plane should be 10 cm.

The test level for ac mains power input ports shall be 1KV open circuit.

Test Setup

Burst on Power Line (direct injection)

Test Results

Adjustment on UCS 500 M4: Trigger "AUTO", Burst length: 15ms		Test Time:		60s for every voltage and polarity 120s for every voltage and polarity				
Testing on power Line (direct injection)		Reaction of The Test Object During and after Test						Result
Test Voltage	Repetition Frequency	L1 =>GND (+ =>GND)	L2=> GND	L3=> GND	N=> GND	PE=> GND	L1, N, => GND	
-0.5kV	5kHz	n.r.r	N/A	N/A	n.r.r	N/A	n.r.r	Pass
+0.5kV	5kHz	n.r.r	N/A	N/A	n.r.r	N/A	n.r.r	Pass
-1.0kV	5kHz	n.r.r	N/A	N/A	n.r.r	N/A	n.r.r	Pass
+1.0kV	5kHz	n.r.r	N/A	N/A	n.r.r	N/A	n.r.r	Pass

Clause 9.5 RF Common Mode**According to EMC basic standard (EN61000-4-6 [10])**

Environmental conditions: Temperature: 23°C; Humidity: 50%RH

USB Dongle Part at Operating Mode

Type of Port: AC mains power input/output port

Performance Criterion: CT/CR

Start Frequency = 150KHz Stop Frequency = 80MHz

Frequency Step = 50kHz in the range of 150kHz-5MHz

1% increment in the range of 5MHz-80MHz

Modulation = AM, 400Hz, 1kHz, 80%

Test Setup

Injection via CDN or BIC clamp

Test Results

Injection On	Injection Via	Reaction of the EUT During and after test	Result
AC input power line	CDN	No reactions recognized	Pass

Clause 9.7 Voltage Dips

According to EMC basic standard (EN61000-4-11 [13])

Environmental conditions: Temperature: 24°C; Humidity: 50%RH

USB Dongle Part at Operating Mode

Type of Port: AC mains power input/output port

Performance Criterion: TT/TR and CT/CR

For the table top EUT the distance to the reference ground plane should be 80 cm.

The test level shall be- a vol. Reduction of the supply vol. 30% for 10ms, 40% for 100ms and 100% for 5000ms

Test Results

Voltage Dip:

Test Level % Ut	Reduction	Duration (periods)	Phase Angle	Reaction of EUT during and after Test	Result
70	30%	10ms	0° - 360°	n.r.r- performance criteria A observed	Pass
40	60%	100ms	0° - 360°	n.r.r- performance criteria A observed	Pass
Voltage Interceptions:					
Test Level % Ut	Reduction	Duration (periods)	Phase Angle	Reaction of EUT during and after Test	Result
0	100%	5000ms	0° - 360°	n.r.r- performance criteria B observed	Pass

Clause 9.8 Surges Common & Differential Mode (1-phase)

According to EMC basic standard (EN61000-4-5 [14])

Environmental conditions: Temperature: 24°C; Humidity: 50%RH

USB Dongle part at Operating Mode

Type of Port: AC mains power input/output port

Performance Criterion: TT/TR

For the table top EUT the distance to the reference ground plane should be 80 cm.

1KV open circuit for common mode & 0.5KV open circuit for differential mode.

Test Results

5 pulses for each polarity and test voltage, alternating and negative/positive, triggered in case of AC- powerline: 0°, 45°, 90°, 180°, 270°, referred to the line frequency. (L1)

Repetition rate is 1 per min.

Test Voltage	Reaction of the test object during and after test by trigger angle/pulse no.(coupling on DC-lines =>trigger angle not relevant).					Result
	0°/pulse no1, 2	45°/pulse, no.3, 4	90°/pulse, no. 5, 6	180°/pulse, no. 7, 8	270°/pulse, no. 9, 10	
Capacitive coupling on AC line: L1=>N or DC lines lines +=>- (Ri=2 Ω /C =18uF)						
-0.5kV	No reaction	No reaction	No reaction	No reaction	No reaction	Pass
+0.5kV	Recognized	Recognized	Recognized	Recognized	Recognized	
-1.0kV	No reaction	No reaction	No reaction	No reaction	No reaction	Pass
+1.0kV	Recognized	Recognized	Recognized	Recognized	Recognized	
-2.0Kv	N/A	N/A	N/A	N/A	N/A	N/A
+2.0kV						
- kV	N/A	N/A	N/A	N/A	N/A	N/A
+kV						

3. CE Mark label specification

Text of the mark is black or white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing and shall be affixed at a conspicuous location on the EUT or silk-screened onto the EUT.



Mark Location: Rear enclosure

4. Photographs - EUT

TX (Mouse + Keyboard)



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.


TX (Keyboard)




The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.




The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.


TX (Mouse)



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.





The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.




The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

RX (Host)



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.



The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

5.0	Test Equipments				
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2017-06-02	2018-06-01
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2017-06-02	2018-06-01
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2017-06-02	2018-06-01
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2017-06-02	2018-06-01
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2017-06-02	2018-06-01
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2017-06-02	2018-06-01
System Controller	CT	SC100	-	2017-08-22	2018-08-21
Oscillator	KENWOOD	AG-203D	3070002	2017-08-22	2018-08-21
Spectrum Analyzer	HAMEG	HM5012	-	2017-08-22	2018-08-21
Power Supply	LW	APS1502	-	2017-08-22	2018-08-21
5K VA AC Power Source	California Instruments	5001iX	56060	2017-06-02	2018-06-01
CDN	EM TEST	CDN M2/M3	-	2017-06-02	2018-06-01
Attenuation	EM TEST	ATT6/75	-	2017-06-02	2018-06-01
Resistance	EM TEST	R100	-	2017-06-02	2018-06-01
Electromagnetic Injection Clamp	LITTHI	EM101	35708	2017-06-02	2018-06-01
Inductive Components	EM TEST	MC2630	-	2017-06-02	2018-06-01
Antenna	EM TEST	MS100	-	2017-06-02	2018-06-01
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	2017-08-22	2018-08-21
Power Amplifier	AR	150W1000	300999	2017-08-22	2018-08-21
Field probe	Holaday	HI-6005	105152	2017-08-22	2018-08-21
Bilog Antenna	Chase	CBL6111C	2576	2017-08-22	2018-08-21
Loop Antenna	EMCO	6502	00042960	2017-08-22	2018-08-21
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2017-08-22	2018-08-21
3m OATS	--	--	N/A	2017-08-24	2018-08-23
Vector Signal Generator	AGILENT	E4438C	MY49070 163	2017.09.20	2018.09.19
Splitter	Mini-Circuits	ZAP-50W	NN256400 424	2017.09.20	2018.09.19

The device described above is tested by Shenzhen SETEK Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen SETEK Technology Co., Ltd.

Directional Coupler	AGILENT	87300C	MY44300 299	2017.09.20	2018.09.19
vector Signal Generator	AGILENT	E4438C	US442719 17	2017.09.20	2018.09.19
4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	AGILENT	U2531A	TW54063 507	2017.09.20	2018.09.19
4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	AGILENT	U2531A	TW54063 513	2017.09.20	2018.09.19
Splitter	Mini	PS3-7	4463	2017.09.20	2018.09.19
Spectrum Analyzer	AGILENT	E7405A	US442104 71	2017.09.20	2018.09.19
Attenuator	Resnet	20dB	(n.a)	2017.09.20	2018.09.19
Signal Analyzer	AGILENT	N9010A	MY480304 94	2017.09.20	2018.09.19
Horn Antenna	ROHDE&SCHWARZ	BBHA 9120D	9120D-631	2017-08-24	2018-08-23

End of the report