

EMC Report

Product: Bluetooth keyboard

Model No.: CND-HBTK7

Additional Model No.: N/A

Trade Mark: N/A

Report No.: TCT190416E002

Issued Date: Apr. 30, 2019

Issued for:

Shen Zhen Newidea Technology Co., Limited
Building 31, No.5 Area, Cuigang Industrial Zone, Fuyong Town, Baoan
District, Shenzhen, China

Issued By:

Shenzhen TCT Testing Technology Co., Ltd.
1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China
TEL: +86-755-27673339
FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen TCT Testing Technology Co., Ltd., This document may be altered or revised by Shenzhen TCT Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS



1. Test Certification	3
2. Test Result Summary	4
3. EUT Description.....	5
4. General Information.....	6
4.1. Test environment and mode.....	6
4.2. Description of Support Units.....	6
4.3. Test Instruments List	7
5. Facilities and Accreditations	9
5.1. Facilities	9
5.2. Location	9
5.3. Measurement Uncertainty.....	9
6. Emission Test	10
6.1. Conducted Emission.....	10
6.2. Radiated Emission	13
6.3. Harmonic Current Emissions	20
6.4. Flicker and Voltage Fluctuation	20
7. Immunity Test	21
7.1. Performance Criteria	21
7.2. Surges	22
7.3. Electrical Fast Transient (EFT).....	22
7.4. Radio-frequency Continuous Conducted (CS)	22
7.5. Voltage Dips and Voltage Interruption	22
7.6. Electrostatic Discharge.....	22
7.7. Radio-frequency Electromagnetic Field Amplitude Modulated (RS)	26
8. Photographs of Test Configuration.....	28
9. Photographs of EUT	30

1. Test Certification

Product:	Bluetooth keyboard
Model No.:	CND-HBTK7
Additional Model No.:	N/A
Trade Mark:	N/A
Applicant:	Shen Zhen Newidea Technology Co., Limited
Address:	Building 31, No.5 Area, Cuigang Industrial Zone, Fuyong Town, Baoan District, Shenzhen, China
Manufacturer:	Shen Zhen Newidea Technology Co., Limited
Address:	Building 31, No.5 Area, Cuigang Industrial Zone, Fuyong Town, Baoan District, Shenzhen, China
Date of Test:	Apr. 17, 2019 – Apr. 29, 2019
Applicable Standards:	Draft ETSI EN 301 489-17 V3.2.0 (2017-03) Draft ETSI EN 301 489-1 V2.2.0 (2017-03)

The above equipment has been tested by Shenzhen TCT Testing Technology Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report is covering the essential requirement of directive 2014/53/EU.

Tested By:**Kevin Huang****Date:****Apr. 29, 2019****Reviewed By:****Ben Zha****Date:****Apr. 30, 2019****Approved By:****Tomsin****Date:****Apr. 30, 2019**

2. Test Result Summary

EMI Test				
Test Item	Test Requirement	Test Method	Application	Result
Radiated Emission	ETSI EN301 489-1	EN 55032	Enclosure	PASS
Conducted Emission	ETSI EN301 489-1	EN 55032	AC port	PASS
Harmonic Current Emissions	ETSI EN301 489-1	EN 61000-3-2	AC port	N/A
Voltage Fluctuations and Flicker	ETSI EN301 489-1	EN 61000-3-3	AC port	N/A
EMS Test				
ESD (Electrostatic Discharge)	ETSI EN301 489-1	EN 61000-4-2	Enclosure	PASS
Radiated Immunity	ETSI EN301 489-1	EN 61000-4-3	Enclosure	PASS
EFT (Electrical Fast Transients)	ETSI EN301 489-1	EN 61000-4-4	AC port	N/A
Surge Immunity	ETSI EN301 489-1	EN 61000-4-5	AC port	N/A
Injected Currents	ETSI EN301 489-1	EN 61000-4-6	AC port	N/A
Voltage Dips and Interruptions	ETSI EN301 489-1	EN 61000-4-11	AC port	N/A
Note: 1 Pass: Test item meets the requirement. 2. N/A: Test case does not apply to the test object. 3. The test result judgment is decided by the limit of test standard.				

3. EUT Description

Product:	Bluetooth keyboard
Model No.:	CND-HBTK7
Additional Model No.:	N/A
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	Bluetooth4.0
Operation Frequency:	2402MHz~2480MHz
Transfer Rate:	1 Mbits/s
Modulation Type:	GFSK
Modulation Technology:	FHSS
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Power Supply:	Rechargeable Li-ion Battery DC 3.7V

4. General Information

4.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	DC 3.7V
Humidity	56%
Atmospheric Pressure:	1008 mbar
Test Mode:	
TM1	Charging + BT

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Notebook Computer	XiaoXin CHAO5000	PF0WZYD9	/	Lenovo
Adapter	ETA0U82CBC	RT10206CS/AE	/	SAMSUNG

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.3. Test Instruments List

Name	Model No.	Manufacturer	Date of Cal.	Due Date
Conducted Emission				
EMI Test Receiver	ESPI	R&S	Jul. 18, 2018	Jul. 17, 2019
LISN-2	NSLK 8126	Schwarzbeck	Sep. 20, 2018	Sep. 19, 2019
Attenuator	10dB	N/A	Sep. 17, 2018	Sep. 16, 2019
Coaxial Cable	N/A	TCT	Sep. 17, 2018	Sep. 16, 2019
Radiated Emission				
EMI Test Receiver	ESIB7	R&S	Jul. 18, 2018	Jul. 17, 2019
Spectrum Analyzer	FSQ40	R&S	Sep. 20, 2018	Sep. 19, 2019
Amplifier	8447D	HP	Sep. 17, 2018	Sep. 16, 2019
Amplifier	EM30265	EM Electronics Corporation CO.,LTD	Sep. 17, 2018	Sep. 16, 2019
Broadband Antenna	VULB9163	Schwarzbeck	Sep. 02, 2018	Sep. 01, 2019
Horn Antenna	BBHA 9120D	Schwarzbeck	Oct. 20, 2018	Oct. 19, 2019
Ultra Broadband ANT	HL562	R&S	Sep. 20, 2018	Sep. 19, 2019
Universal Radio Communication Tester	CMU200	R&S	Sep. 20, 2018	Sep. 19, 2019
Coaxial Cable	N/A	TCT	Sep. 17, 2018	Sep. 16, 2019
Coaxial Cable	N/A	TCT	Sep. 17, 2018	Sep. 16, 2019
Coaxial Cable	N/A	TCT	Sep. 17, 2018	Sep. 16, 2019
Coaxial Cable	N/A	TCT	Sep. 17, 2018	Sep. 16, 2019
Loop antenna	ZN30900A	ZHINAN	Oct. 20, 2018	Oct. 19, 2019
Electrostatic Discharge				
Electrostatic Discharge Generator	ESD61002AG	Prima	Sep. 27, 2018	Sep. 26, 2019
Continuous Radiated Disturbances				
Signal Generator	2022D	Maconi	Sep. 27, 2018	Sep. 26, 2019
Power Amplifier	A00181-1000	M2S	Sep. 27, 2018	Sep. 26, 2019
Power Amplifier	AC8113/800-250A	M2S	Sep. 27, 2018	Sep. 26, 2019
Power Antenna	CBL6140A	SCHAFFNER	Sep. 27, 2018	Sep. 26, 2019
Universal Radio Communication Tester	CMU200	R&S	Sep. 20, 2018	Sep. 19, 2019

Audio Analyzer	UPL 16	Rohde & Schwarz	Sep. 27, 2018	Sep. 26, 2019
MOUTH SIMULATOR	B&K	4227	N/A	N/A
SOUND LEVEL CALIBRATOR	B&K	4231	N/A	N/A
Antenna Tripod	TP1000A	Amplifier Research	N/A	N/A
High Gain Horn Antenna (0.8-6GHz)	AT4002A	Amplifier Research	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen TCT Testing Technology Co., Ltd.

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

5.3. Measurement Uncertainty


The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Temperature	$\pm 0.1^{\circ}\text{C}$
2	Humidity	$\pm 1.0 \%$
3	Spurious Emissions, Conducted	$\pm 2.56 \text{ dB}$
4	All Emissions, Radiated	$\pm 4.28\text{dB}$

6. Emission Test

6.1. Conducted Emission


6.1.1. Test Specification

Test Requirement:	ETSI EN 301 489-1		
Test Method:	EN 55032		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity: Class B	Class B		
Receiver Setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Setup:	 <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test Procedure	<p>The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to EN55032 Class B on conducted measurement.</p>		
Test Instrument:	Refer to section 4.3 for details		
Test Mode:	Refer to section 4.1 for details		
Test Results:	PASS		

6.1.2. Test Data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **L1** Temperature: 25
Limit: EN55032 Class B Conduction(QP) Power: Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.6540	33.67	10.23	43.90	56.00	-12.10	peak	
2		1.3200	28.13	10.39	38.52	56.00	-17.48	peak	
3		2.1614	27.98	10.45	38.43	56.00	-17.57	peak	
4		2.9940	27.55	10.46	38.01	56.00	-17.99	peak	
5		3.7905	27.34	10.47	37.81	56.00	-18.19	peak	
6		7.2870	27.41	10.51	37.92	60.00	-22.08	peak	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Lisen factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)


Q.P. =Quasi-Peak

AVG =average

Any value more than 10dB below limit have not been specifically reported.

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 25
Limit: EN55032 Class B Conduction(QP) Power: Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2220	25.58	10.23	35.81	62.74	-26.93	peak	
2	*	0.6585	29.04	10.23	39.27	56.00	-16.73	peak	
3		1.1220	23.40	10.37	33.77	56.00	-22.23	peak	
4		1.9635	21.85	10.45	32.30	56.00	-23.70	peak	
5		4.7355	21.06	10.48	31.54	56.00	-24.46	peak	
6		10.1760	24.36	10.57	34.93	60.00	-25.07	peak	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Lisen factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

Q.P. =Quasi-Peak



AVG =average

Any value more than 10dB below limit have not been specifically reported.

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.2. Radiated Emission

6.2.1. Test Specification

Test Requirement:	ETSI EN 301 489-1				
Test Method:	EN 55032				
Test Frequency Range:	30MHz to 6GHz				
Test Site:	Measurement Distance: 3m				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Average		1MHz	10Hz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-230MHz		40.0		Quasi-peak Value
	230MHz-1GHz		47.0		Quasi-peak Value
	1GHz-3GHz		50.0		Average Value
			70.0		Peak Value
	3GHz-6GHz		54.0		Average Value
			74.0		Peak Value
Test Setup:	Below 1GHz				
					
Test Setup:	Above 1GHz				
					

For 3m distance description:




Figure C.1 – Measurement distance

Test Procedure:

From 30MHz to 1GHz:

1. The radiated emissions test was conducted in a semi-anechoic chamber.
2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
3. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT.
4. The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.


Above 1GHz:

1. The radiated emissions test was conducted in a fully-anechoic chamber.
2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
3. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emission spectrum plots of the EUT.
4. The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements

	were performed for both horizontal and vertical antenna polarization.
Test Instrument:	Refer to section 4.3 for details
Test Mode:	Refer to section 4.1 for details
Test Results:	PASS

6.2.2. Test Data

Radiated Emission In Horizontal (30MHz----1000MHz)



Site: Polarization: **Horizontal** Temperature: 25
Limit: EN 55032 ClassB 3M Radiation Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	114.8224	44.13	-10.16	33.97	40.00	-6.03	QP
2		127.5865	45.68	-14.48	31.20	40.00	-8.80	QP
3		158.6400	45.08	-15.87	29.21	40.00	-10.79	QP
4		343.6505	45.10	-9.84	35.26	47.00	-11.74	QP
5		409.6505	47.23	-8.83	38.40	47.00	-8.60	QP
6		512.9477	43.84	-7.30	36.54	47.00	-10.46	QP

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss


Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

* is meaning the worst frequency has been tested in the test frequency range

Radiated Emission In Vertical (30MHz----1000MHz)



Site: Polarization: **Vertical** Temperature: 25
 Limit: EN 55032 ClassB 3M Radiation Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		99.0690	33.43	-8.22	25.21	40.00	-14.79	QP
2	*	121.4622	44.10	-12.11	31.99	40.00	-8.01	QP
3		139.7908	46.80	-16.07	30.73	40.00	-9.27	QP
4		145.8109	48.03	-16.19	31.84	40.00	-8.16	QP
5		461.6313	41.96	-8.11	33.85	47.00	-13.15	QP
6		578.0358	37.54	-6.32	31.22	47.00	-15.78	QP

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss


Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

* is meaning the worst frequency has been tested in the test frequency range

Radiated Emission In Horizontal (1000MHz----6000MHz)



Site: Polarization: **Horizontal** Temperature: 25
 Limit: EN 55032 ClassB 3M Radiation 1-6G(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1555.281	50.53	-11.84	38.69	70.00	-31.31	peak
2		1861.144	50.61	-11.44	39.17	70.00	-30.83	peak
3	*	2525.403	50.77	-6.82	43.95	70.00	-26.05	peak
4		3629.378	47.63	-2.55	45.08	74.00	-28.92	peak
5		4281.201	43.33	2.76	46.09	74.00	-27.91	peak
6		5705.837	39.45	8.11	47.56	74.00	-26.44	peak

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss


Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

* is meaning the worst frequency has been tested in the test frequency range

Radiated Emission In Vertical (1000MHz----6000MHz)



Site: Polarization: **Vertical** Temperature: 25
 Limit: EN 55032 ClassB 3M Radiation 1-6G(peak) Power: Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		1271.983	49.25	-12.02	37.23	70.00	-32.77	peak
2		1776.264	50.53	-12.20	38.33	70.00	-31.67	peak
3		2410.229	48.31	-7.37	40.94	70.00	-29.06	peak
4	*	2894.601	47.91	-6.17	41.74	70.00	-28.26	peak
5		4421.814	39.34	2.98	42.32	74.00	-31.68	peak
6		5604.311	37.18	7.59	44.77	74.00	-29.23	peak

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

* is meaning the worst frequency has been tested in the test frequency rang

6.3. Harmonic Current Emissions

6.3.1. Test Specification

Test Result:	EUT belongs to portable equipment, Not applicable
---------------------	---

6.4. Flicker and Voltage Fluctuation

6.4.1. Test Specification

Test result:	EUT belongs to portable equipment, Not applicable
---------------------	---

7. Immunity Test

7.1. Performance Criteria

Performance Criteria of ETSI EN 301 489-1, sub clause 6

Criteria	Performance Criteria
CT/CR	During and after the test, the apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a permissible performance level specified by the manufacturer when the apparatus is used as intended. In some cases this permissible performance level may be replaced by a permissible loss of performance.
TT/TR	After the test, the apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a permissible performance level specified by the manufacturer, when the apparatus is used as intended. In some cases this permissible performance level may be replaced by a permissible loss of performance.

Performance Criteria of ETSI EN 301 489-17, sub clause 6

Criteria	Performance Criteria
CT/CR	The performance criteria A shall apply. Tests shall be repeated with the EUT in standby mode (if applicable) to ensure that unintentional transmission does not occur. In systems using acknowledgement signals, it is recognized that an acknowledgement (ACK) or Not acknowledgement (NACK) transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.
TT/TR	The performance criteria B shall apply, except for voltage dips of 100 ms and voltage interruptions of 5 000 ms duration, for which performance criteria C shall apply. Tests shall be repeated with the EUT in standby mode (if applicable) to ensure that unintentional transmission does not occur. In systems using acknowledgement signals, it is recognized that an acknowledgement (ACK) or not-acknowledgement (NACK) transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.

7.2. Surges

7.2.1. Test Specification

Test result:	EUT belongs to portable equipment, Not applicable
---------------------	---

7.3. Electrical Fast Transient (EFT)

7.3.1. Test Specification

Test result:	EUT belongs to portable equipment, Not applicable
---------------------	---

7.4. Radio-frequency Continuous Conducted (CS)

7.4.1. Test Specification

Test result:	EUT belongs to portable equipment, Not applicable
---------------------	---

7.5. Voltage Dips and Voltage Interruption

7.5.1. Test Specification


Test result:	EUT belongs to portable equipment, Not applicable
---------------------	---

7.6. Electrostatic Discharge

7.6.1. Test Specification

Test Requirement:	EN 301489-1
Test Method:	EN 61000-4-2
Discharge Voltage:	Contract Discharge: $\pm 2\text{kV}$, $\pm 4\text{kV}$ Air Discharge: $\pm 2\text{kV}$, $\pm 4\text{kV}$, $\pm 8\text{kV}$ HCP/VCP: $\pm 2\text{kV}$, $\pm 4\text{kV}$
Polarity:	Positive & Negative
Number of Discharge:	Contact Discharge: Minimum 25 times at each test point, Air Discharge: Minimum 10 times at each test point.
Discharge Mode:	Single Discharge
Discharge Period:	1 second minimum

Test Setup:



Test Procedure:

1) Air discharge:

The test was applied on non-conductive surfaces of EUT. The round discharge tip of the discharge electrode was approached as fast as possible to touch the EUT. After each discharge, the discharge electrode was removed from the EUT. The generator was re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure was repeated until all the air discharge completed

2) Contact Discharge:

The test was applied on conductive surfaces of EUT. the generator was re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. the tip of the discharge electrode was touch the EUT before the discharge switch was operated.

3) Indirect discharge for horizontal coupling plane

At least 10 single discharges shall be applied at the front edge of each HCP opposite the centre point of each unit of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge. Consideration should be given to exposing all sides of the EUT.

4) Indirect discharge for vertical coupling plane

At least 10 single discharges were applied to the centre of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, was placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges were applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

Test Instrument:

Refer to Section 4.3 for Details

Test Mode:

Refer to Section 4.1 for Details




Test Results:

PASS

7.6.2. Test data


Test points:	I: Please refer to red rings as below plots			
	II: Please refer to yellow rings as below plots			
Air Discharge				
Discharge Voltage (KV)	Type of discharge	Test points	Observation s (Performanc e Criterion)	Result
± 2, ± 4	Contact	II	TT/TR	PASS
± 2, ± 4,± 8	Air	I	TT/TR	PASS
Indirect Discharge				
Discharge Voltage (KV)	Type of discharge	Test points	Observation Performance	Result
± 2, ± 4	HCP-Bottom/Top/ Front/Back/Left/ Right	Edge of the HCP	TT/TR	PASS
± 2, ± 4	VCP-Front/Back /Left/Right	Centre of the VCP	TT/TR	PASS

Test point as follows:



7.7. Radio-frequency Electromagnetic Field Amplitude Modulated (RS)

7.7.1. Test Specification

Test Requirement:	ETSI EN 301 489-1
Test Method:	EN 61000-4-3
Frequency Range:	80MHz to 6.0GHz
Test Level:	3V/m
Modulation:	80%, 1kHz Amplitude Modulation
Test Setup:	
Test Procedure:	<ol style="list-style-type: none"> 1. For table-top equipment, the EUT was placed in the chamber on a non-conductive table 0.8m high. For arrangement of floor-standing equipment, the EUT was mounted on a non-conductive support 0.1m above the supporting plane. For human body-mounted equipment, the EUT may be tested in the same manner as table top items. 2. If possible, a minimum of 1 m of cable is exposed to the electromagnetic field. Excess length of cables interconnecting units of the EUT shall be bundled low-inductively in the approximate centre of the cable to form a bundle 30 cm to 40 cm in length. 3. The EUT was initially placed with one face coincident with the calibration plane. The EUT face being illuminated was contained within the UFA (Uniform Field Area). 4. The frequency ranges to be considered were swept with the signal modulated and pausing to adjust the RF signal level or to switch oscillators and antennas as necessary. Where the frequency range was swept incrementally, the step size was not exceeding 1 % of the preceding frequency value. 5. The dwell time of the amplitude modulated carrier at each frequency was not be less than the time necessary for the EUT to be exercised and to respond, and was not less than

	<p>0,5 s.</p> <p>6. The test normally was performed with the generating antenna facing each side of the EUT.</p> <p>7. The polarization of the field generated by each antenna necessitates testing each selected side twice, once with the antenna positioned vertically and again with the antenna positioned horizontally.</p> <p>The EUT was performed in a configuration to actual installation conditions, a video camera and/or audio monitor were used to monitor the performance of the EUT.</p>
Test Instrument:	Refer to Section 4.3 for Details
Test Mode:	Refer to Section 4.1 for Details
Test Result:	PASS

7.7.2. Test data


Frequency	Level	Modulation	Antenna Polarization	EUT Face	Observations (Performance Criterion)
80 MHz-6.0GHz	3 V/m	1 kHz, 80 % Amp. Mod, 1 % increment, dwell time=3 seconds	V	Front	CT/CR
			H		
			V	Rear	
			H		
			V	Left	
			H		
			V	Right	
			H		
			V	Top	
			H		
			V	Bottom	
			H		

8. Photographs of Test Configuration

Radiated Emission



CE



ESD



9. Photographs of EUT



Outside View













Inside View











*****END OF REPORT*****